

MV cables Tools

MF3/60-SR



Certifications

Approved by ENEDIS

Section

MV Multifunction

Application

Field
Laboratory



PRODUCT BENEFITS

Tuning of the pitch of the tool
Embedded wear pads to protect the tool from the contact with the outer sheath
For thick insulation

TOOL CAPACITY

Diameter 16 - 58 mm
0,630 - 2,283 inch

Pelable semicon thickness capacity 0.4 - 1.5 mm

Insulation thickness capacity 11 mm

Stylus included SR

TOOL DIMENSIONS

Length 305 mm

Width 115 mm

Height 165 mm

Weight without box 1,75 Kg

Packaging Box

ALROC SAS

Z.I. de la Fonderie - 72160 TUFFE
FRANCE

Phone: +33 2 43 71 11 80

Fax number : +33 2 43 71 16 51

www.alroc.fr

Multifunction tool for outer sheath, peelable semiconductor and thick insulation

TO DO WHAT

The MF3/60-SR tools enables the user to :
Remove the outer sheath (PE-PVC-PR) with a straight and neat cut
Score the peelable semiconductor (with the SR scoring stylus delivered with the tool)
Set the length to be removed and remove thicker insulation with a straight and neat cut



Options

SRC - Scoring stylus for peelable semiconductor with chamfer
SCH - Chamfering stylus for insulation

Spare part

KIT-MF3/40 - Protective wear pads
SR - Scoring stylus for peelable semiconductor
LS - Spare blade for peelable semiconductor
LMF2-S - Spare blade for outer sheath and thick insulation
BR - Thrust to set the length of insulation to be remove
VBB1 - Screw for locking the thrust
PCR - Quick set up right angled 45° handle
196855 - Straight handle M10
108098 - Clamping knob for blade

Associated tool

ALROC-FENTE - Tool to perform slits on cable's outer sheath
ROTO-TMG - Connector holder for bolted and clamping connections
DSP - Peelable semiconductor lifter



Part Number	Diameter	Tool capacity			Dimensions			Packaging
		Pelable semicon thickness capacity	Insulation thickness capacity	Stylus included	Length	Width	Height	
MF3/40	16 - 40 mm 0,630 - 1,575 in	0.4 - 1.5 mm	7 mm	SR	305 mm 12,008 in	100 mm 3,937 in	165 mm 6,496 in	box
MF3/40-C	16 - 40 mm 0,630 - 1,575 in	0.4 - 1.5 mm	7 mm	SRC	305 mm 12,008 in	100 mm 3,937 in	165 mm 6,496 in	box
MF3/40-SR	16 - 40 mm 0,630 - 1,575 in	0.4 - 1.5 mm	11 mm	SR	305 mm 12,008 in	100 mm 3,937 in	165 mm 6,496 in	box
MF3/40-SRC	16 - 40 mm 0,630 - 1,575 in	0.4 - 1.5 mm	11 mm	SRC	305 mm 12,008 in	100 mm 3,937 in	165 mm 6,496 in	box
MF3/40-SSR	16 - 40 mm 0,630 - 1,575 in	Option	7 mm	None	305 mm 12,008 in	100 mm 3,937 in	165 mm 6,496 in	box
MF3/60	16 - 58 mm 0,630 - 2,283 in	0.4 - 1.5 mm	7 mm	SR	305 mm 12,008 in	115 mm 4,528 in	165 mm 6,496 in	box
MF3/60-C	16 - 58 mm 0,630 - 2,283 in	0.4 - 1.5 mm	7 mm	SRC	305 mm 12,008 in	115 mm 4,528 in	165 mm 6,496 in	box
MF3/60-SR	16 - 58 mm 0,630 - 2,283 in	0.4 - 1.5 mm	11 mm	SR	305 mm 12,008 in	115 mm 4,528 in	165 mm 6,496 in	box
MF3/60-SRC	16 - 58 mm 0,630 - 2,283 in	0.4 - 1.5 mm	11 mm	SRC	305 mm 12,008 in	115 mm 4,528 in	165 mm 6,496 in	none
MF3/60-SSR	16 - 58 mm 0,630 - 2,283 in	Option	7 mm	None	305 mm 12,008 in	115 mm 4,528 in	165 mm 6,496 in	none