

# CURRENT TRANSFORMERS

We have several types of current transformers with standard ratios in stock. Splittable CT's are delivered with 4 m cable.

Temperature range: -30°C to 80°C

Isolation level: 3 kV

Please contact us for other versions, the products beneath are standard products kept in stock!

## Split core current transformers, clip-together, for cables with diameter <34 mm

Article number:	606550
Ratio:	150/1
Continuous overload:	133% (200 A)
Diameter:	40 mm
Opening:	34 mm

Article number:	60651
Ratio:	300/1
Continuous overload:	133% (400 A)
Diameter:	40 mm
Opening:	34 mm



## Split core current transformers, taped, for cables with diameter <50 mm or 85 mm

Diameter:	50 mm
Opening:	44 mm

Article number:	606571
Ratio:	300/1
Continuous overload:	120% (360 A)
Diameter:	85 mm
Opening:	44 mm

Article number:	606572
Ratio:	300/1
Continuous overload:	133% (400 A)
Diameter:	50 mm
Opening:	44 mm



## Solid current transformers

Article number: 606560  
Ratio: 150/1  
Continuous overload: 120% (180 A)  
Diameter: 45 mm

Article number: 606561  
Ratio: 300/1  
Continuous overload: 120% (360 A)  
Diameter: 45 mm

